

ACCESSORIES

MS Polymer Accessories Polypropylene Primer

WIKO MS Polymer - Polypropylene Primer is a one-component primer which particularly is used to improve the adhesion in combination with plastics.

Trading unit:
250ml can (brush cap)
1000ml can

Item no.:
MSPP.PP.PD250
MSPP.PP.D1000



Specific Properties

Provides good adhesive strength in combination with several plastics, especially polypropylene.

Application

The surface has to be clean, dry and free of dust and grease.

Apply the primer with a brush or a lint-free cloth onto the surface so that it is fully wetted. Evaporation time after application is at least 15 minutes.

The bonding/ sealing should be realised within 6 hours after applying.

Avoid contact with the pre-treated surface, because this might impair the adhesion strength.

Shake the can before handling and close it immediately after usage.

Ensure the compatibility of sensitive materials before using.

Shelf Life

Shelf life: 12 months (in unopened original packaging)

Technical Data

Density:	Approx. 0,88 g/ml
Colour:	aluminium coloured
Solid content:	Approx. 4%
Curing time:	Min. approx. 15 minutes
Working temperature:	+ 5 °C to + 35 °C
Storage temperature:	+ 5 °C to + 30 °C

The information contained in this data sheet, especially the suggestions for processing and application of products, is based on our experience and newest expertise. Due to the facts that materials can be very diverse and that we have no influence on the working conditions, we recommend to perform sufficient tests to validate the compatibility of the products. Our company shall neither be held liable for this information nor for a verbal or written consultation. Additionally, please consider the information of our safety data sheets.